

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/717,579	11/21/2000	Curtis E. Jutzi	042390.P9907	2132	
8791	7590 08/25/2006		EXAMINER		
BLAKELY	BLAKELY SOKOLOFF TAYLOR & ZAFMAN			VU, NGOC K	
12400 WILS SEVENTH F	HIRE BOULEVARD		ART UNIT	PAPER NUMBER	
~ — · — · · ·	LES, CA 90025-1030		2623		

DATE MAILED: 08/25/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	plication No. Applicant(s)	
Office Action Commons	09/717,579	JUTZI, CURTIS E.	
Office Action Summary	Examiner	Art Unit	
	Ngoc K. Vu	2623	
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address	
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING D/ - Extensions of time may be available under the provisions of 37 CFR 1.1: after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period v - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133)	
Status			
1) Responsive to communication(s) filed on 30 M	av 2006		
<u> </u>	action is non-final.		
3) Since this application is in condition for allowar		ecoution as to the morite in	
closed in accordance with the practice under E			
	.x pane Quayle, 1955 C.D. 11, 40	13 O.G. 213.	
Disposition of Claims			
4) Claim(s) <u>1-3,6-17,20-31,34-45 and 48-55</u> is/are	e pending in the application.		
4a) Of the above claim(s) is/are withdraw	vn from consideration.		
5) Claim(s) is/are allowed.			
6) Claim(s) <u>1-3,6-17,20-31,34-45 and 48-55</u> is/are	e rejected.		
7) Claim(s) is/are objected to.			
8) Claim(s) are subject to restriction and/or	r election requirement.		
Application Papers			
9) The specification is objected to by the Examine	r		
10) The drawing(s) filed on is/are: a) acce		Evaminor	
Applicant may not request that any objection to the			
Replacement drawing sheet(s) including the correct		• •	
11) The oath or declaration is objected to by the Ex			
	animer. Note the attached Office	Action of form PTO-152.	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority documents	s have been received.		
2. Certified copies of the priority documents			
3. Copies of the certified copies of the prior		d in this National Stage	
application from the International Bureau	• • • • • • • • • • • • • • • • • • • •	•	÷
* See the attached detailed Office action for a list	of the certified copies not receive	d.	
Attachment(s)			
Notice of References Cited (PTO-892)	4) Interview Summary	(PTO-413)	
2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s)/Mail Da	ite	
I) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	5) Notice of Informal Pa	atent Application (PTO-152)	
Potent and Tradeural Office			

Art Unit: 2623

DETAILED ACTION

Claim Rejections - 35 USC § 101

1. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

2. Claims 29-31 and 34-42 are rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter as follows.

Claim 29 defines a machine-readable medium embodying functional descriptive material. However, the claim does not define a computer-readable medium or memory and is thus non-statutory for that reason (i.e., "When functional descriptive material is recorded on some computer-readable medium it becomes structurally and functionally interrelated to the medium and will be statutory in most cases since use of technology permits the function of the descriptive material to be realized"). The examiner suggests amending the claims to embody the program on "computer-readable medium" or equivalent in order to make the claims statutory. Any amendment to the claims should be commensurate with theirs corresponding disclosure.

Claim 29 drawn to functional descriptive material recorded on a machine-readable medium. Normally, the claim would be statutory. However, the specification defines the instructions are tangibly embodied in and/or readable from a machine-readable medium, device or carrier (page 17, lines 9+), and the program or code segments can be stored in a machine readable medium, such as a processor readable medium or a computer program product, or transmitted by a computer data signal embodied in a carrier wave, or a signal modulated by a carrier, etc. (page 23, lines 3+). (Emphasis added).

It is noted that a "signal" embodying functional descriptive material is neither a process

nor a product (i.e., a tangible "thing") and therefore does not fall within one of the four statutory classes of § 101. Rather, "signal" is a form of energy, in the absence of any physical structure or tangible material.

Because the full scope of the claims as properly read in light of the disclosure encompasses non-statutory subject matter, the claims as a whole are non-statutory. The examiner suggests amending the claims to *include* the disclosed tangible computer readable media, while at the same time *excluding* the intangible media such as signals, carrier waves, etc defined in the specification. Any amendment to the claims should be commensurate with theirs corresponding disclosure. For example, in claim 29, the phrase "A machine-readable medium" should be changed to --A computer-readable medium--. And all recitations of "machine" should be changed to --computer--.

Claim Rejections - 35 USC § 112

- The following is a quotation of the second paragraph of 35 U.S.C. 112:
 The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
- 4. Claims 1-3, 6-17, 20-31, 34-45 and 48-55 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 1 is indefinite because there is no antecedent basis for the limitation "the service level" in line 4.

Claim 1 recites the limitation "the service level of a digital television broadcast signal being received on a channel" in line 4. In light of the specification, the specification at page 8, first paragraph, describes that a digital television receiver receives a digital television broadcast signal which includes a data test stream. A service level determiner is used to determine a

service level of the digital television broadcast signal base upon a loss of data packets from the data test stream. That is, the service level determiner determines a service level of the received digital television broadcast signal. With respect to claim 1, it is unclear whether "a digital television broadcast signal" in line 4 and "a digital television broadcast signal" in line 2 are the same. Therefore, this renders claim 1 as being indefinite.

Claim 15 recites the limitation "a service level of a digital television broadcast signal being received on a channel" in lines 3-4. In light of the specification, the specification at page 8, first paragraph, describes that a digital television receiver receives a digital television broadcast signal which includes a data test stream. A service level determiner is used to determine a service level of the digital television broadcast signal base upon a loss of data packets from the data test stream. That is, the service level determiner determines a service level of the received digital television broadcast signal. With respect to claim 15, it is unclear whether "a digital television broadcast signal" in lines 3-4 and "a digital television broadcast signal" in line 2 are the same. Therefore, this renders claim 15 as being indefinite.

Claim 29 recites the limitation "a service level of a digital television broadcast signal being received on a channel" in lines 4-5. In light of the specification, the specification at page 8, first paragraph, describes that a digital television receiver receives a digital television broadcast signal which includes a data test stream. A service level determiner is used to determine a service level of the digital television broadcast signal base upon a loss of data packets from the data test stream. That is, the service level determiner determines a service level of the received digital television broadcast signal. With respect to claim 29, it is unclear whether "a digital television broadcast signal" in lines 4-5 and "a digital television broadcast signal" in line 3 are the same. Therefore, this renders claim 29 as being indefinite.

Art Unit: 2623

Page 5

Claim 29 recites the limitation "a service level of a digital television broadcast signal being received on a channel" in lines 4-5. In light of the specification, the specification at page 8, first paragraph, describes that a digital television receiver receives a digital television broadcast signal which includes a data test stream. A service level determiner is used to determine a service level of the digital television broadcast signal base upon a loss of data packets from the data test stream. That is, the service level determiner determines a service level of the received digital television broadcast signal. With respect to claim 29, it is unclear whether "a digital television broadcast signal" in lines 4-5 and "a digital television broadcast signal" in line 3 are the same. Therefore, this renders claim 29 as being indefinite.

Claim 43 recites the limitation "a service level of a digital television broadcast signal being received on a channel" in line 5. In light of the specification, the specification at page 8, first paragraph, describes that a digital television receiver receives a digital television broadcast signal which includes a data test stream. A service level determiner is used to determine a service level of the digital television broadcast signal base upon a loss of data packets from the data test stream. That is, the service level determiner determines a service level of the received digital television broadcast signal. With respect to claim 43, it is unclear whether "a digital television broadcast signal" in line 5 and "a digital television broadcast signal" in line 3 are the same. Therefore, this renders claim 43 as being indefinite.

Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

6. Claims 1, 6-15, 20-29, 34-43 and 48-55 are rejected under 35 U.S.C. 103(a) as being unpatentable over Anderson et al. (US 5,905,713 A) in view of Gusella et al. (US 5,408465 A) and further in view of Gangitano (US 6,580,452 B1).

Regarding claim 1, Anderson teaches an apparatus (figures 1 & 5) comprising:

a digital television receiver (64 within device 63) to receive a digital television broadcast signal, the digital television broadcast signal including a data test stream (38) having a plurality of data packets used to determine the service level of a digital television broadcast signal being received on a channel (determining errors in the packet stream of the digital broadcast signal being received on a carrier frequency - see col. 5, lines 1-7 and figure 1; col. 2, line 49 to col. 3, line 18; col. 5, lines 50-52), and

an analyzer logic (68) to verify the integrity of the digital television broadcast signal and to cause the verification error or results to be displayed (see col. 6, lines 1-6, 40-43, 55-57);

wherein the analyzer logic measures a number of data packets of the data test stream received by the digital television receiver over predetermined interval (it is noted that the verify function tests the semantics and sequencing of the sequencing of the packet stream over a predetermined interval, i.e., before displaying the verification results – see col. 6, lines 44-52; col. 7, lines 32-36).

Anderson does not teach determining a data packet loss percentage value for the data stream by calculating a ratio of the measured number of data packets received by the digital receiver and a number of data packets that should have been received by the digital receiver. However, Gusella discloses that a data loss ratio could be measured as a ratio of lost packets to successfully received packets (see col. 8, lines 19-22). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by measuring a data loss ratio as a ratio of lost packets to successfully received

packets as disclosed Gusella in order to accurately determine error of data reception in the network.

Anderson does not teach displaying a service level of signal based upon a loss of data packets. However, Gangitano teaches detecting a loss of received signal and presenting a signal loss on-screen notification (see col. 2, lines 45-50 and figure 5). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by detecting a loss of received signal and presenting a signal loss on-screen notification as taught Gangitano in order to effectively provide an improved means for displaying received signal strength.

Regarding **claim 15**, Anderson teaches a method comprising:

receiving a digital television broadcast signal that includes a data test stream (38) having a plurality of data packets, the data test stream used to determine the service level of a digital television broadcast signal being received on a channel (determining errors in the packet stream of the digital broadcast signal being received on a carrier frequency - see col. 5, lines 1-7 and figure 1; col. 2, line 49 to col. 3, line 18; col. 5, lines 50-52);

determining the integrity of the digital television broadcast signal via an analyzer logic and to cause the verification error or results to be displayed (see col. 6, lines 1-6, 40-43, 55-57);

wherein the analyzer logic measures a number of data packets of the data test stream received by the digital television receiver over predetermined interval (it is noted that the verify function tests the semantics and sequencing of the sequencing of the packet stream over a predetermined interval, i.e., before displaying the verification results – see col. 6, lines 44-52; col. 7, lines 32-36).

Anderson does not teach determining a data packet loss percentage value for the data stream by calculating a ratio of the measured number of data packets received by the digital receiver and a number of data packets that should have been received by the digital receiver. However, Gusella discloses that a data loss ratio could be measured as a ratio of lost packets to successfully received packets (see col. 8, lines 19-22). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by measuring a data loss ratio as a ratio of lost packets to successfully received packets as disclosed Gusella in order to accurately determine error of data reception in the network.

Anderson does not teach displaying a service level of signal based upon a loss of data packets. However, Gangitano teaches detecting a loss of received signal and presenting a signal loss on-screen notification (see col. 2, lines 45-50 and figure 5). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by detecting a loss of received signal and presenting a signal loss on-screen notification as taught Gangitano in order to effectively provide an improved means for displaying received signal strength.

Regarding **claim 29**, Anderson discloses a machine-readable medium having stored thereon instructions (software or programs stored within device 63 – see figure 5), which when executed by a processor, causes the processor to perform the following: receiving a digital television broadcast signal that includes a data test stream (38) having a plurality of data packets, the data test stream used to determine the service level of a digital television broadcast signal being received on a channel (determining errors in the packet stream of the digital broadcast signal being received on a carrier frequency - see col. 5, lines 1-7 and figure 1; col. 2, line 49 to col. 3, line 18; col. 5, lines 50-52);

Art Unit: 2623

determining the integrity of the digital television broadcast signal via an analyzer logic and to cause the verification error or results to be displayed (see col. 6, lines 1-6, 40-43, 55-57);

wherein the analyzer logic measures a number of data packets of the data test stream received by the digital television receiver over predetermined interval (it is noted that the verify function tests the semantics and sequencing of the sequencing of the packet stream over a predetermined interval, i.e., before displaying the verification results – see col. 6, lines 44-52; col. 7, lines 32-36).

Anderson does not teach determining a data packet loss percentage value for the data stream by calculating a ratio of the measured number of data packets received by the digital receiver and a number of data packets that should have been received by the digital receiver. However, Gusella discloses that a data loss ratio could be measured as a ratio of lost packets to successfully received packets (see col. 8, lines 19-22). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by measuring a data loss ratio as a ratio of lost packets to successfully received packets as disclosed Gusella in order to accurately determine error of data reception in the network.

Anderson does not teach displaying a service level of signal based upon a loss of data packets. However, Gangitano teaches detecting a loss of received signal and presenting a signal loss on-screen notification (see col. 2, lines 45-50 and figure 5). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by detecting a loss of received signal and presenting a signal loss on-screen notification as taught Gangitano in order to effectively provide an improved means for displaying received signal strength.

Regarding claim 43, Anderson teaches a system comprising:

a digital television receiver (64 – see figure 5) to receive a digital television broadcast signal, the digital television broadcast signal including a data test stream (38) having a plurality of data packets used to determine the service level of a digital television broadcast signal being received on a channel (determining errors in the packet stream of the digital broadcast signal being received on a carrier frequency - see col. 5, lines 1-7 and figure 1; col. 2, line 49 to col. 3, line 18; col. 5, lines 50-52), and

an analyzer logic (68) to verify the integrity of the digital television broadcast signal and to cause the verification error or results to be displayed (see col. 6, lines 1-6, 40-43, 55-57);

wherein the analyzer logic measures a number of data packets of the data test stream received by the digital television receiver over predetermined interval (it is noted that the verify function tests the semantics and sequencing of the sequencing of the packet stream over a predetermined interval, i.e., before displaying the verification results – see col. 6, lines 44-52; col. 7, lines 32-36).

Anderson does not teach determining a data packet loss percentage value for the data stream by calculating a ratio of the measured number of data packets received by the digital receiver and a number of data packets that should have been received by the digital receiver. However, Gusella discloses that a data loss ratio could be measured as a ratio of lost packets to successfully received packets (see col. 8, lines 19-22). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by measuring a data loss ratio as a ratio of lost packets to successfully received packets as disclosed Gusella in order to accurately determine error of data reception in the network.

Anderson does not teach displaying a service level of signal based upon a loss of data packets. However, Gangitano teaches detecting a loss of received signal and presenting a signal loss on-screen notification (see col. 2, lines 45-50 and figure 5). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Anderson by detecting a loss of received signal and presenting a signal loss on-screen notification as taught Gangitano in order to effectively provide an improved means for displaying received signal strength.

Regarding claims 6-8, 20-22, 34-36 and 48-50, the combined teachings of Anderson, Gusella and Gangitano include measuring a data loss ratio as a ratio of lost packets to successfully received packets and presenting a signal loss on-screen notification to indicate the service level of the digital television broadcast signal (see Anderson: col. 6, lines 44-52; col. 7, lines 32-36; Gusella: col. 8, lines 19-22; Gangitano: col. 2, lines 45-50 and figure 5).

Regarding **claims 9, 23, 37 and 51**, the combined teaching of Anderson and Gusella as modified by Gangitano shows signal loss on-screen notification (see Gangitano: figure 5). They fail to teach a bar shape meter indicating a service level range from 0% to 100%. It would have been obvious to one of ordinary skill in the art to modify the combined system of Anderson, Gusella and Gangitano by providing a bar shaped meter indicating the reception condition range from 0%-100" in order to visually provide the reception condition in an accurate manner.

Regarding claims **10, 24, 38 and 52**, the combined system of Anderson, Gusella and Gangitano includes that the service level is updated at predetermined intervals, e.g., per unit time when deterring the received packet stream (see Anderson: col. 5, lines 50-52).

Art Unit: 2623

Regarding **claims 11, 25, 39 and 53**, the combined system of Anderson, Gusella and Gangitano teaches that the display device is a television (see Anderson: figure 1; Gangitano: figures 3-5).

Regarding claims 12, 14, 26, 28, 40, 42 and 54, the combined system of Anderson,
Gusella and Gangitano teaches receiving the broadcast signal via a terrestrial broadcast station
network (see Anderson: col. 3, lines 50-54).

Regarding claims **13, 27, 41 and 55**, the combined system of Anderson, Gusella and Gangitano teaches receiving the broadcast signal via a satellite network (see col. 3, lines 45-50).

7. Claims 2, 3, 16, 17, 30, 31, 44 and 45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Anderson et al. (US 5,905,713 A) in view of Gusella et al. (US 5,408465 A) and further in view of Gangitano (US 6,580,452 B1) and further in view of Mao et al. (U.S. 6,459,427 B1).

Regarding claims 2, 3, 16, 17, 30, 31, 44 and 45, Anderson does not explicitly disclose the data stream includes an Internet Protocol (IP). However, Mao discloses a digital TV receiver for receiving Internet data over digital broadcast TV network. Basically, the data and control information can be carried over MPEG-2 transport streams. The HTML pages and their control map information are either mapped directly onto the sections of the MPEG-2 transport stream or mapped through an intermediate layer such as UDP/IP and then encapsulated in the sections of the MPEG-2 transport stream. Mao further discloses that on the client side, a control block 240 allows the consumer to navigate 250 according to particular protocols 260, for example, UDP, and/or IP 270 (see abstract; col. 6, lines 7-12; col. 7-8, lines 63-3). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the combined system of Anderson, Gusella and Gangitano by providing IP data with MPEG-2

transport streams as disclosed by Mao in order greatly desired to provide Internet service with the television program to the consumer over digital broadcast TV network.

Further regarding claims 3,17, 31 and 45, the combined system of Anderson, Gusella and Gangitano as modified by Mao further includes the MPEG-2 is segmented and carried over MPEG-2 transport packets, which can be filtered through the PID (packetID) by the decoder (see Mao: col. 8, lines 5-8).

Response to Arguments

8. Applicant's arguments filed 5/30/06 have been fully considered but they are not persuasive.

Applicant argues that Anderson does not teach or suggest a data test stream having a plurality of data packets used to determined service level of a digital television signal being received on a channel. This argument is not persuasive based on the following reasons.

Anderson further discloses that each of the packet streams 38 are modulated onto a carrier frequency The carrier is upconverted in frequency to one of assigned uplink frequencies between 17.3 to 17.8 GHz. The signals are uplinks to a satellite 23 to transmit to receiver 24 (see col. 5, lines 1-7 and figure 1). Thus, the packet stream 38 is considered a digital television broadcast signal being provided on a carrier frequency or a channel.

According to the specification, the present invention measures the data packet loss (i.e., the error rate) of the data test stream and a representation of the service level is displayed to the user (specification: pages 9+). Thus, determining the service level relates to determining or detecting error in transmitting/receiving signal.

Anderson's system allows a user to monitor and display the status of the packet data stream being received, wherein a packet stream analyzer performs verification tests and displays any errors. It is noted that the integrity of the packet stream is monitored after it has

been transmitted and received. (See col. 2, line 49 to col. 3, line 18; col. 5, lines 50-52). That is, the system of Anderson detects and/or determines errors in packet stream being received. With respect to the context of the claim, determining errors in the packet stream being received as disclosed by Anderson equates to "service level". Accordingly, Anderson teaches determining errors in the packet stream of the digital broadcast signal being received on a carrier frequency.

In response to applicant's argument that the examiner's conclusion of obviousness is based upon improper hindsight reasoning, it must be recognized that any judgment on obviousness is in a sense necessarily a reconstruction based upon hindsight reasoning. But so long as it takes into account only knowledge which was within the level of ordinary skill at the time the claimed invention was made, and does not include knowledge gleaned only from the applicant's disclosure, such a reconstruction is proper. See *In re McLaughlin*, 443 F.2d 1392, 170 USPQ 209 (CCPA 1971).

In response to applicant's arguments against the references individually, one cannot show nonobviousness by attacking references individually where the rejections are based on combinations of references. See *In re Keller*, 642 F.2d 413, 208 USPQ 871 (CCPA 1981); *In re Merck & Co.*, 800 F.2d 1091, 231 USPQ 375 (Fed. Cir. 1986).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ngoc K. Vu whose telephone number is 571-272-7306. The examiner can normally be reached on Monday-Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, John W. Miller can be reached on 571-272-7353. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 09/717,579 Page 15

Art Unit: 2623

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Ngoc K. Vu Primary Examiner

Art Unit 2623

August 21, 2006